

E4.2N 3200 Ekip Dip Lsig 4p F HR

new.abb.com/products/es/1SDA071773R1/e4-2n-3200-ekip-dip-lsig-4p-f-hr

Información detallada para: E4.2N 3200 Ekip Dip Lsig 4p F HR

Información General

- **Tipo de producto extendido:**
E4.2N 3200 Ekip Dip Lsig 4p F HR
- **Código de producto:**
1SDA071773R1
- **EAN:**
8015644756239
- **Descripción corta:**
E4.2N 3200 Ekip Dip Lsig 4p F HR
- **Descripción larga:**
C.BREAKER SACE EMAX2 E4.2N 3200 FIXED FOUR-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/DIP-LSIG R 3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Productos » Productos y sistemas de baja tensión » Interruptores automáticos » Interruptores automáticos de bastidor abierto » Emax 2



Dimensiones / Peso

510 mm x 371 mm x 270mm / 70 kg

Información de Embalaje

- **Embalaje Nivel 1**

515 x 610 x 785 mm / 77 kg

Ambiente

RoHS Status:

Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Información Adicional

- **Current Type:**

AC

- **Electrical Durability:**

Ue =< 440 V 7000 cycle

Ue = 500 ... 690 V 7000 cycle

20 cycles per hour

- **Mechanical Durability:**

20000 cycle

60 cycles per hour

- **Neutral Pole Current ([%Iu]):**

100 %

- **Number of Poles:**

4

- **Power Loss:**

425 W

- **Product Main Type:**

SACE Emax 2

- **Product Name:**

Air Circuit Breaker

- **Product Type:**
Air Circuit Breaker
- **Rated Service Short-Circuit Breaking Capacity, in % of I_{cu} (I_{cs}):**
100 %
- **Rated Current (I_n):**
3200 A
- **Rated Voltage (U_r):**
690 V
- **Rated Impulse Withstand Voltage (U_{imp}):**
acc. to IEC 60947-2 12 kV
- **Rated Insulation Voltage (U_i):**
AC 1000 V
- **Rated Operational Voltage:**
690 V AC
- **Rated Service Short-Circuit Breaking Capacity (I_{cs}):**
(220 V AC) 66 kA
(230 V AC) 66 kA
(380 V AC) 66 kA
(400 V AC) 66 kA
(415 V AC) 66 kA
(440 V AC) 66 kA
(500 V AC) 66 kA
(660 V AC) 66 kA
(690 V AC) 66 kA
- **Rated Short-time Withstand Current (I_{cw}):**
for 1 s 66 kA
for 3 s 50 kA
- **Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):**
(400 V AC) 66 kA
(415 V AC) 66 kA
(440 V AC) 66 kA
(500 V AC) 66 kA
(525 V AC) 66 kA
(690 V AC) 66 kA

- **Rated Uninterrupted Current (I_U):**
3200 A
- **Release:**
Ekip Dip LSIG
- **Release Type:**
EL
- **Short-Circuit Performance Level:**
N
- **Standards:**
IEC
- **Sub-type:**
E4.2
- **Terminal Connection Type:**
Rear flat Horizontal
- **Version:**
F

Certificados y Declaraciones (Número de Documento)

- **Ficha técnica, información técnica:**
1SDC200023D0709
- **Declaración de conformidad - CE:**
9AKK106713A5545
- **Environmental Information:**
Not Available
- **Instrucciones y manuales:**
1SDH001000R0005