

FICHA DEL PRODUCTO

ITEM:

Interruptor MCCB 4P LS/I 40-100A 36KA NXMS-160F

CÓDIGO:

07222436100CH

IMAGEN:



CHINT
CHINT ELECTRIC

DESCRIPCIÓN
APLICACIÓN:

Corriente nominal I_n (A), 40°C, 55°C:	100A
Poder de corte:	230V/50kA ; 415V/36kA
Unidad de disparo:	Ekip Dip LSI/I
Sobrecarga (I_r / LTM – Long Time Delay):	$I_r = 0,4...1 \times I_n$
Cortocircuito selectiv (I_{sd} / STM – Short Time Delay):	$I_{sd} = (1.5-2-3-4-5-6-8)I_r + OFF$
Cortocircuito instantáneo (I_i / INST):	$I_i = (2-3-4-6-8-10-12)I_r + OFF$
Polos:	4P
Tensión nominal U_e (V), CA50/60Hz:	220/230/240, 380/400/415/500
Tensión U_{imp} (kV):	8kV
Tensión aislamiento U_i (V):	800V
Temperatura:	-35°C~+70°C
Distancia de Arco:	≤50
Vida Mecánica:	20000
Vida Eléctrica:	10000
Norma:	IEC/EN 60947-2

Medidas:	Ancho:	120
	Alto:	155
	Profundidad:	91

