

FICHA DEL PRODUCTO

ITEM:

CÓDIGO:

IMAGEN:



DESCRIPCIÓN
APLICACIÓN:

Desconectador en 3 o 4 polos
AC21 / AC22 / AC23
Hasta 690V
Montaje a placa, incluye manilla para puerta y eje extensor

| Tipo | 400 V | | 400 V | | AC-23 | AC-23 | | Cod. NDU | Peso kg | |
|---------------|-----------|----------------|-----------|----------------|-----------|----------------|----------------|----------|-------------|-----|
| | AC-21 | 415 V 690 V | AC-22 | 415 V 690 V | | 400 V 415 V | 690 V 690 V | | | |
| | I_n / A | | I_n / A | | I_n / A | P / kW | I_n / A | P / kW | | |
| 3-pole | | | | | | | | | | |
| VKE 3250 | 250 A | | 250 A | | 250 A | 132 kW | 250 A | 250 kW | 170433025KA | 4,0 |
| 4-pole | | | | | | | | | | |
| VKE 4250 | 250 A | | 250 A | | 250 A | 132 kW | 250 A | 250 kW | 170443025KA | 4,6 |
| 3-pole | | | | | | | | | | |
| VKE 3400 | 400 A | | 400 A | | 400 A | 200 kW | 400 A | 355 kW | 170433040KA | 4,6 |
| 4-pole | | | | | | | | | | |
| VKE 4400 | 400 A | | 400 A | | 400 A | 200 kW | 400 A | 355 kW | 170443040KA | 5,4 |

