



Part No.: 32426

EQUES®PowerConnector

empty adapter as component support

to prepare pre-assembled motor circuit protection units for the 60 mm system,

for busbars 5 or 10 mm thick and special profiles double or triple T,

without electrical contacts,

combination base for 5 and 10 mm thick busbars

in 12 mm width

System :

60mm-System classic

Standards :

IEC / EN 60439-1

Approvals :

Germanischer Lloyd, GOST, CSA, UL (approved for feeder circuits to UL 508A up to 600 V)

Type No.: EMC6000-L

Customs Tariff: 8536 90 85

UL File Number: E123577, Category: NMTR, www.ul.com

CSA File Number: 110285, Class Number: 3211-37, <http://directories.csa-international.org>

The product must not be CCC certified

Electrical Data :

Mechanical Data :

Width x Height x Depth (mm): 54 x 260 x 75

Weight (g): 421

2 adjustable mounting rails

Material Characteristics :

Main body:

temperature stability 120°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 200,
halogen-free

DIN rail:

temperature stability 100°C,
fire behaviour UL 94 HB,
creepage resistance CTI 200,
halogen-free

Remarks :

to make compact and complete motor circuit protection units with common switchgear and to mount and to connect them safely to the busbar system, test position with break of the supply lines

Accessories to Article 32426 :

32969 end stop for mounting rail

32948 mounting rail 54 mm
for EEC, EMC and EEP