

# FICHA DEL PRODUCTO

ITEM:

Interrupor horario dig 2 canales 24-264V diario/semanal

CÓDIGO:

2716006FTR

IMAGEN:



### Symbol legend

1 2 3 4 5 6 7 — Days of the week Monday, Tuesday, ...Sunday

C1 — Channel 1

C2 — Channel 2

On OFF — Relay status

☀ — Automatic mode

☾ — Manual mode

🏠 — Holiday mode

❄ — Winter time

☀ — Summer time

Prog — Program setting

### Maximum pilotable power

2300W	2300W	1000W	500W	500W

DESCRIPCIÓN  
APLICACIÓN:

Supply terminals	A1-A2
Rated voltage	AC/DC 24-264V
Rated frequency	50/60Hz
Power consumption	2W
Supply voltage tolerance	±10%
Number of channels	Double channels
Number of programs	100
Program	weekly program, daily program
Mode of work	manual, automatic, holiday
Summer/winter time	off, automatic changes
Time tolerance	≤1s/day at 25°C
Power reserve	10 year
Data readout	LCD display with backlight
Number of contacts	SPDT x2
Current of contacts	16A/250V AC1
Switching capacity	4000VA/AC1, 384W/DC
Mechanical life	10 <sup>6</sup>
Electrical life	10 <sup>5</sup>
Rated insulation voltage	250V
Protection degree	IP20
Pollution degree	3
Altitude	≤2000m
Ambient temperature	-20°C~55°C
Permissible relative humidity	≤50%(40°C,without condensation)
Storage temperature	-30°C~70°C
Wire size	1mm <sup>2</sup> ~ 4mm <sup>2</sup>
Tightening torque	0.5Nm
Mounting	TH-35 Rail(EN60715)
Dimensions	90*36*64mm
Standard	IEC60947-1/IEC60947-2-7

### Wiring diagram

