

## Halogen Free Flame-retardant Normal Wall Heat Shrinkable Tube(metric) ◀

## Halogen Free Flame-retardant Normal Wall Heat Shrinkable Tube( inch) ◀

Inch	Size (mm)	As Supplied (mm)		After Recovery (mm)		Standard Package			Application Range (mm)
		I.D.	Average W.T.	Max. I.D.	Average W.T.	M/spool	Spools/carton	Carton size(cm)	
3/64	Φ0.8	1.0±0.2	0.15±0.05	≤0.50	0.22±0.10	200	23	31×31×44.5	0.6~0.8
1/16	Φ1.0	1.5±0.3	0.15±0.05	≤0.65	0.28±0.10	200	16	31×31×44.5	0.75~0.9
3/32	Φ2.0	2.5±0.3	0.18±0.05	≤1.00	0.35±0.10	200	15	46×46×44.5	1.1~1.8
1/8	Φ3.0	3.5±0.4	0.18±0.05	≤1.50	0.40±0.10	200	11	46×46×44.5	1.6~2.7
3/16	Φ4.5	5.0±0.4	0.25±0.05	≤2.30	0.50±0.10	100	10	46×46×44.5	2.35~4.0
1/4	Φ6.0	6.5±0.4	0.28±0.05	≤3.0	0.55±0.10	100	7	46×46×44.5	3.1~5.4
3/8	Φ9.0	9.5±0.5	0.30±0.08	≤4.5	0.60±0.10	100	12	46×46×31	4.7~8.0
1/2	Φ12	12.5±0.5	0.30±0.08	≤6.0	0.60±0.10	100	10	46×46×31	6.2~11
3/4	Φ18	19.0±0.7	0.40±0.15	≤9.0	0.80±0.15	100	7	46×46×29.5	9.3~17
1	Φ25	26.0±0.7	0.55±0.15	≤12.5	0.90±0.15	50	6	46×46×31	12.8~24
1-1/4	Φ28	29.0±0.7	0.55±0.15	≤14.0	0.90±0.15	50	5	46×46×29.5	14.4~29
1-1/2	Φ40	41.5±0.7	0.55±0.15	≤20.0	1.00±0.15	50	4	46×46×31	21~39
2	Φ50	51.0±0.7	0.55±0.15	≤25.0	1.00±0.15	25	5	46×46×44.5	26~49
3	Φ80	≥80	0.70±0.15	≤41.0	1.46±0.20	25	3	31×31×42	45~75
4	Φ100	≥100	0.70±0.20	≤51.0	1.46±0.20	25	2	31×31×34.5	55~95
5	Φ120	≥120	0.70±0.20	≤61.0	1.56±0.20	15	2	31×31×40.5	65~115

