

# FICHA DEL PRODUCTO

ITEM: Calefactor FHST 250Vac, riel DIN, IP20, c/ventilador

CÓDIGO:

IMAGEN:



DESCRIPCIÓN  
APLICACIÓN:

Features	Unit	5107250AP	5107500AP
Heating Capacity	W	250	500
Power supply	V/Hz	230/50-60	230/50-60
Max. current	A	1.2	2.4
Heating element type	-	Resistor	
Thermal protection	-	Fusible Termico	
Radiator	-	Extruded aluminium profile, anodized	
Axial fan	-	Rodamiento, 50.000 hrs a 25°C air flow rate 35 m <sup>3</sup> /h, free flow	
Signalling	-	Green LED power ON	
Electrical connections	-	3 terminales para cable de 2.5 mm <sup>2</sup>	
Protection class IEC	-	Class I, aterrizado	
Protection degree EN60529	-	IP20	
Operating temperature	°C (°F)	-25/+70 (-13/+158)	
Storage temperature	°C (°F)	-45/+80 (-49/+176)	
Mounting	-	DIN rail 35 mm EN50022	
Installation position	-	mejor en vertical	
Dimensions HxWxD	mm	135x112x82	165x112x82
Weight (with packaging)	kg	0.88(0.94)	0.97(1.04)
Conformity	-	CE - UL 	

