



ALFATORR14

ROOF FANS



Features	Unit	ALFATORR1450	ALFATORR1451
Air flow rate (free blow)	m ³ /h	1500/(1550)	1500/(1550)
Flow rate with filter fan	m ³ /h	900/(950)	900/(950)
Power supply	V/Hz	230-50/60	115-50/60
Dimensions HxWxD	mm	540x390x128	540x390x128
Power consumption	W	160/(215)	160/(215)
Current consumption	A	0.70/(0.98)	1.40/(1.96)
Overcurrent protection	-	thermal	thermal
Electric connection	-	4-pole terminal	4-pole terminal
Duty cycle	-	100%	100%
Operating temperature	°C	-20/+50	-20/+50
Protection degree enclosure side/class	-	IP44/Class I	IP44/Class I
Noise level	dB(A)	74/(75)	74/(75)
Flow direction	-	inside-out	inside-out
Bearing	-	ball	ball
Service life (at 40°C)	hr	50,000	50,000
Material	-	metal	metal
Gasket	-	PVC	PVC
Weight (with packaging)	kg	11.3(12.3)	11.3(12.3)
Package dimensions	mm	550x400x140	550x400x140
Mounting	-	Screws	Screws
Conformity/Approvals	-	CE	

Versions

RAL7035 - Code ending	B	B
-----------------------	---	---

Accessories

Thermostat 0-60°C, N. Open	THV02	THV02
Grill with filter mat	ALFA3000BP	ALFA3000BP

