



413.1666

BASE EMPOTRABLE

16A 3P+T 6h 380-415V 50Hz 60Hz 70X87MM
Bornes con tornillo

TECHDATA		STANDARDS AND LAWS	
Tipo de producto	BASE EMPOTRABLE	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Serie comercial	Serie OPTIMA	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descripción sintética	BASE EMPOTRABLE		
Intensidad nominal	16A		
Polos	3P+T	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Posición de hora	6h	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Tensión nominal (range)	250-400V		
Tensión nominal	380-415V		
Frecuencia nominal	50Hz	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Frecuencia nominal	60Hz	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Color	ROJO		
Material	TERMOPLÁSTICO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Grado de protección	Splash proof		
Grado de protección IP	IP44/IP54		
Grado de protección IK	IK08		
Tipos de salidas disponibles	INCLINADA		
Bornes	Bornes con tornillo		
Material de los contactos	CuZn (latón)		
Brida de Fijación	70X87MM		